



**HAYWARD PLASTICS** (A division of B C Electrical Techniques Ltd.)  
 Pembroke Road  
 Stocklake  
 Aylesbury  
 HP20 1DE

Tel: 01296 481995  
 Fax: 01296 394158  
 enquiries@hayward-plastics.co.uk  
 www.hayward-plastics.co.uk

**Quickshrink is a semi-rigid thin walled PVC sleeving frequently known as "Layflat"**

**rapid shrinkdown and a hard finish at low cost**

Quickshrink sleeveings are very thin walled typically 0.1mm (100 microns) and this is reflected in the low price.

**• applications**

The very fast shrinkdown coupled with its thin wall has made Quickshrink ideal for its main uses:


- |                          |   |
|--------------------------|---|
| battery packing          | sizes available for all common cell sizes |
| tamper proofing          | usually with a perforation strip          |
| point-of-sale protection | avoids direct handling of product         |
| decorative finish        | brightly coloured and glossy surface      |

**boxing**

In many applications it is often necessary to use a Quickshrink with narrow diameter. These are difficult to open because the sleeving is rigid. Hayward have resolved this problem with its unique Boxing process. The sleeving is supplied cut to length as specified by the customer and also opened into a four-sided Box shape to provide easy covering.

**• property summary**

- |                        |                |
|------------------------|----------------|
| operating temperatures | -20C to 85°C   |
| tensile strength       | 45MPa          |
| dielectric strength    | 13kV/mm        |
| shrink temperature     | 100°C to 130°C |
| radial shrinkage       | up to 50%      |



**• colour range**

Hayward have stocks of several opaque colours including red, yellow, green, blue, white, grey and black. There are also stocks of transparent colours. The colours are at various Layflat widths which meet many current market needs. Special colour/size variations can be made. Clear Quickshrink has very high transparency.

**• sizes available**

By convention, Quickshrink is specified by its Layflat Width unlike Polyshrink and Rayshrink (the flexible sleeveings) which are sold by diameter.

**layflat width**

the smallest layflat width in stock is 6.5mm to cover a diameter of about 4mm  
 the largest layflat width in stock is 200mm to cover a diameter of about 125mm

**wall thickness**

Quickshrink can be made with wall thicknesses from 0.05mm wall (50 micron) to 0.3mm wall (300 micron). These are available ex-stock in particular combinations of layflat and colour.

**• Ordering Code.**

Please order by quoting layflat width, wall thickness and colour

**example:**

for a layflat of 57mm and wall thickness of 0.15mm Quickshrink 57 x 0.15 white